

Nuline[®]

ULTRA-SS

Salient Features :

- Easy to use
- Built in Calibration Procedure
- Digital Display-2 line,
- 16 Character LCD Display
- Built in Reports
 - Acknowledgment Slip :
 - Shift Summary
 - Milk Bill
 - Payment Summary
- Easy to Clean - Single Cell
- Suitable for Cow/Buffalo/Mixed Milk
- Fast and Accurate
- Small and Portable
- Measurement Time -35-40 seconds
- (According to Milk Temp.)
- Average Speed min. 85 Samples per Hours.
- RS 232 Interface
- 12th Month Warranty



Technical Specifications

Parameter	Range	Resolution	Accuracy
Fat	0 ~ 15%	0.01%	±0.10%
SNF	0 ~ 12%	0.01%	±0.20%
CLR	0 ~ 40%	0.1	±0.50
Added Water	0 - 100%	1.0%	±0.30%
Repeatability	± 0.05%		
Accuracy*	± 0.10%		
Sample Volume	20 ml		
AC Power Supply (Optional)	110 ~ 270 Volts AC		
DC Power Supply	12 Volt DC		
Power Consumption	30 Watt		
Ambient Air Temperature	15°C to 50°C		
Dimension	240mm x 160mm x 320mm		
Weight	2.8 Kgs Approx		
Ports	RS 232 Serial / Printer		
Relative Humidity	30% to 80%		
Milk Temperature	5°C to 40°C		

Loose Accessories

- RS 232 Serial Cable 1 No.
- Measuring Mug 2 No.
- Battery Power Cable 1 No.
- Plunger 1 No.
- Operating Manual (English) 1 No.
- Daily Cleaning Chemical 2 No.
- Weekly Cleaning Chemical 1 No.



304 STAINLESS STEEL